

Streuereinstellungen

Maschinen- und Antriebstechnik GmbH & Co. KG

Güstrow

Korn - Kali 40 % / Kamex `gran`

K+S

	(m)	Normalstreuen					Randstreuen		Grenzstreuen	
		Streumenge (kg/ha)					Streumenge (kg/ha)		Streumenge (kg/ha)	
		250	400	600	750	-	250 - 500	500 - 750	250 - 500	500 - 750
S t r e u - b r e i t e	12	+30 / 2	+30 / 2	+30 / 2	+30 / 2	-	960 / 0	960 / 0	-	-
	18	+30 / 2	+30 / 2	+50 / 3	+50 / 3	-	960 / 4	960 / 2	960 / 0	800 / 0
	24	(+60 / 3)	(+60 / 3)	(+60 / 3)	-	-	960 / 4	960 / 4	960 / 2	-
	28	(+60 / 3)	(+60 / 3)	-	-	-	Normalstr.	-	960 / 4	-
	32	(+60 / 3)	(+30 / 2)	-	-	-	Normalstr.	-	960 / 4	-
S b	36	(+30 / 2)	(+30 / 2)	-	-	-	Normalstr.	-	Normalstr.	-

() = Variationskoeffizient zwischen 15 % und 25 %

60er Kali `gran`

K+S

	(m)	Normalstreuen					Randstreuen		Grenzstreuen	
		Streumenge (kg/ha)					Streumenge (kg/ha)		Streumenge (kg/ha)	
		200	350	500	-	-	200 - 500	-	200 - 500	-
S t r e u - b r e i t e	12	+30 / 3	+30 / 3	+30 / 3	-	-	960 / 0	-	-	-
	18	+30 / 3	+30 / 3	+30 / 3	-	-	960 / 2	-	650 / 0	-
	24	+30 / 3	+30 / 3	+30 / 3	-	-	960 / 3	-	960 / 0	-
	28	+30 / 3	+30 / 3	+30 / 3	-	-	960 / 4	-	960 / 2	-
	32	+20 / 3	+20 / 3	+20 / 3	-	-	960 / 4	-	960 / 4	-
S b	36	+10 / 3	+10 / 3	+10 / 3	-	-	Normalstr.	-	960 / 4	-

Patentkali

K+S

	(m)	Normalstreuen					Randstreuen		Grenzstreuen	
		Streumenge (kg/ha)					Streumenge (kg/ha)		Streumenge (kg/ha)	
		400	600	800	-	-	400 - 600	600 - 800	400 - 600	600 - 800
S t r e u - b r e i t e	12	+30 / 2	+30 / 2	+30 / 2	-	-	960 / 0	960 / 0	-	-
	18	+30 / 2	+30 / 2	+30 / 2	-	-	960 / 4	960 / 2	960 / 0	800 / 0
	24	+30 / 1	(+30 / 2)	(+30 / 2)	-	-	960 / 4	960 / 4	960 / 2	960 / 1
	28	+30 / 2	+30 / 2	-	-	-	Normalstr.	-	960 / 4	-
	32	+30 / 2	+30 / 2	-	-	-	Normalstr.	-	Normalstr.	-
S b	36	-	-	-	-	-	-	-	-	-

() = Variationskoeffizient zwischen 15 % und 25 %

Kieserit `gran`

K+S

	(m)	Normalstreuen					Randstreuen		Grenzstreuen	
		Streumenge (kg/ha)					Streumenge (kg/ha)		Streumenge (kg/ha)	
		200	350	500	-	-	200 - 500	-	200 - 500	-
S t r e u - b r e i t e	12	+10 / 3	+10 / 3	+10 / 3	-	-	960 / 0	-	-	-
	18	+10 / 3	+10 / 3	+10 / 3	-	-	960 / 2	-	650 / 0	-
	24	+10 / 3	+10 / 3	0 / 2	-	-	960 / 3	-	960 / 0	-
	28	+10 / 3	+20 / 3	0 / 2	-	-	960 / 4	-	960 / 2	-
	32	+10 / 3	-	-	-	-	960 / 4	-	960 / 4	-
S b	36	+10 / 3	-	-	-	-	960 / 4	-	960 / 4	-

Streubild - Einstellwerte gelten für geschärfte Flügelscheiben, Streuscheibendrehzahl 960 U/min, Fahrgeschwindigkeit 12,3 km/h und gut granulierten, staubfreien Dünger